






RoHS
Compliant
2011/65/EU



PCB Layout(Pattern side)

NO. 1	
PART NO	vigor
1	90±30
2	130±30
3	180±30
4	250±30
5	350±50

Specifications:

Electrical:

Rating: DC 12V 50mA

Contact Resistance: 100mΩ Max

Insulation Resistance: 100mΩ Min


Withstand Voltage: AC250V 1minute

Mechanical:

Operating Stroke: 0.25±0.1mm

Operating Force: See chart

Operating Life: 100,000 cycles



Circuit Diagram

GENERAL TOLERANCES		
ANGLES	ANG.	±5°
LINEAR	X.	±0.30
	X.X	±0.25
	X.XX	±0.20
SCALE	1:1	UNIT:mm
	SIZE:A4	SHEET:1/1

DRAW:	Jebnn 2013/01/12
CHKD:	Lucky 2013/01/12
APPROVED:	Allen 2013/01/13
	www.htnn.com.tw

HTNN

TITLE:
TACT SWITCH

PART NO.: TS1102ATx
DWG NO.: HTS1102AT

REV	ECN NO.	DATE	DESCRIPTION	CHANGE	DATE
A			NEW		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO HTNN TECHNOLOGY CO.,LTD, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION