



RoHS
Compliant
2011/65/EU

Specifications:

Electrical:

Rating: DC 12V 50mA

Contact Resistance: 100mΩ Max

Insulation Resistance: 100mΩ Min



Withstand Voltage: AC250V 1minute

Mechanical:


Operating Stroke: 0.25±0.1mm

Operating Force: See chart



Operating Life: 100,000 cycles



PCB Layout (Pattern Side)



Circuit diagram



NO.1	
PART NO	vigor
4	200±50

GENERAL TOLERANCES		
ANGLES	ANG.	±5°
LINEAR	X.	±0.30
	X.X	±0.25
	X.XX	±0.20
SCALE	1:1	UNIT:mm
SIZE:A4	SHEET:1/1	

DRAW:	Jebnn 2014/05/16
CHKD:	Lucky 2014/05/16
APPROVED:	Allen 2014/05/17
www.htnn.com.tw	

HTNN

TITLE:
TACT SWITCH

PART NO.: TS1111SPx
DWG NO.: HTS1111SP

REV	ECN NO.	DATE	DESCRIPTION	CHANGE	DATE
A			NEW		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO HTNN TECHNOLOGY CO.,LTD, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION